HD Series

FEATURES

3 - 5 GPM @ 2700 to 4000 PSI Recoil or electric-start gas engine models



PRESSURE WASHERS / SINCE 1970

COLD WATER

HD 3.0

MODULAR DESIGN FOR EASY TRANSITION BETWEEN CART AND SKID STYLE.

GAS

50 ft.wire-braided hose includes guards,couplers and swivels at both ends

Electric start models include battery

Flat free tires are puncture proof and ready to roll when you need them

Heavy-duty Triplex pump comes with 7-year warranty

.....

Reliable **Honda GX and Vanguard** commercial-duty gasoline engines with 3-year warranty Fatigue-free spring-loaded trigger gun with spray wand and side handle making for easy pointand-shoot cleaning action

Four, high-pressure **stainless steel nozzles**: 15°, 25°, 40° and a detergent nozzle

.....

Low profile $\ensuremath{\textbf{handle}}$ is easy to push and pull

Durable VRT3 **unloader** with bypass loop diverts water flow when trigger gun is not activated

Durable weld free, corrosion resistant **aluminum frame**

Modular design converts to skid

S OF THE REPORT OF THE REPORT

Shown with optional hose reel bracket kit installed

DIRECT/BELT DRIVE



OPTIONS FOR HD SERIES

Skids (with water tank and hose reels) Hose Reel Bracket Kit - for belt or direct drive Skid Mount Feet Hose Hook Wand Holder Handle with Hose Reel

HOTSY.COM NOTHING CLEANS LIKE A HOTSY!



The perfect accompaniment to Hotsy HD Series pressure washers – these mild steel skids offer two configurations: skid with a 50 gallon water tank and 100' hose reel OR skid with two 100' hose reels.



HD SERIES Cold-Water Models

MODULAR PRESSURE WASHERS FOR HEAVY-DUTY CLEANING.

Honda & Vanguard Engines, 6.5 -13 HP 3 to 5 GPM @ 2700 to 4100 PSI Compact/Modular Design

| MODEL | PART NO. | GPM | PSI | ENGINE MODEL | CCs | START | PUMP MODEL | DRIVE | HOSE (FT) | DIMENSIONS (LXWXH) | SHIP WT (LBS) |
|----------------|-------------|-----|------|--------------|-----|----------|------------|--------|--------------|-----------------------|------------------|
| HD 3.0/27 G | 9.807-711.0 | 3.0 | 2700 | Honda GX200 | 196 | Recoil | LP3035 | Direct | 50 | 41"x22"x24" | 112 |
| HD 3.5/35 G | 9.807-712.0 | 3.5 | 3500 | Honda GX270 | 270 | Recoil | LP3535G.1 | Direct | 50 | 41"x22"x24" | 130 |
| HD 3.5/35 G | 1.107-421.0 | 3.5 | 3500 | Vanguard 300 | 305 | Recoil | LP3535G.1 | Direct | 50 | 41"x22"x24" | 130 |
| HD 4.0/40 G | 9.807-713.0 | 4.0 | 4000 | Honda GX390 | 389 | Recoil | LS4040G.3 | Direct | 50 | 43"x26"x27" | 149 |
| HD 4.0/40 G | 1.107-429.0 | 4.0 | 4000 | Vanguard 400 | 408 | Recoil | LS4040G.3 | Direct | 50 | 43"x26"x27" | 149 |
| HD 4.0/40 Ge* | 9.807-714.0 | 4.0 | 4000 | Honda GX390 | 389 | Electric | LS4040G.3 | Direct | 50 | 43"x26"x27" | 158 |
| HD 4.0/40 Ge* | 1.107-435.0 | 4.0 | 4000 | Vanguard 400 | 408 | Electric | LS4040G.3 | Direct | 50 | 43"x26"x27" | 158 |
| HD 3.0/27 GB | 9.807-715.0 | 3.0 | 2700 | Honda GX200 | 196 | Recoil | LP3035G | Belt | 50 | 41"x22"x24" | 123 |
| HD 3.5/35 GB | 9.807-716.0 | 3.5 | 3500 | Honda GX270 | 270 | Recoil | LM3540R.3 | Belt | 50 | 41"x22"x24" | 156 |
| HD 3.5/35 GB | 1.107-422.0 | 3.5 | 3500 | Vanguard 300 | 305 | Recoil | LM3540R.3 | Belt | 50 | 41"x22"x24" | 156 |
| HD 4.0/40 GB | 9.807-717.0 | 4.0 | 4000 | Honda GX390 | 389 | Recoil | LM3840R.3 | Belt | 50 | 43"x26"x27" | 160 |
| HD 4.0/40 GB | 1.107-430.0 | 4.0 | 4000 | Vanguard 400 | 408 | Recoil | LM3840R.3 | Belt | 50 | 43"x26"x27" | 160 |
| HD 4.0/40 GeB* | 9.807-718.0 | 4.0 | 4000 | Honda GX390 | 389 | Electric | LM3840R.3 | Belt | 50 | 43"x26"x27" | 196 |
| HD 4.0/40 GeB* | 1.107-434.0 | 4.0 | 4000 | Vanguard 400 | 408 | Electric | LM3840R.3 | Belt | 50 | 43"x26"x27" | 196 |
| HD 5.0/30 GB | 9.808-251.0 | 5.0 | 3000 | Honda GX390 | 389 | Recoil | LM4035.R3 | Belt | 50 | 43"x26"x27" | 160 |
| HD 5.0/30 GB | 1.107-446.0 | 5.0 | 3000 | Vanguard 400 | 408 | Recoil | LM4035.R3 | Belt | 50 | 43"x26"x27" | 160 |
| HD 5.0/30 GeB* | 9.808-387.0 | 5.0 | 3000 | Honda GX390 | 389 | Electric | LM4035.R3 | Belt | 50 | 43"x26"x27" | 160 |
| HD 5.0/30 GeB* | 9.808-390.0 | 5.0 | 3000 | Vanguard 400 | 408 | Electric | LM4035.R3 | Belt | 50 | 43"x26"x27" | 160 |

*Battery included on electric start models.

DETERGENTS



To clean like a pro, you need to include detergents. Hotsy offers a full line of detergents for cleaning grease, dirt, road grime, aluminum, sanitation and so much more. Our detergents help you clean faster and save money.

PARTS & ACCESSORIES



HOTSY.COM Tel: 800.525.1976 Email: info@hotsy.com

Clean faster and more efficiently with pressure washer accessories like flat surface cleaners and turbo nozzles.

SERVICE



Hotsy factory-trained technicians keep your equipment running with on-site or in shop maintenance and tuneups. Plus, we repair all brands.



NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +_10% and in some cases are tighter within +_ 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 20243 Kärcher North America P/N HOT_HDSG Effective 01/24

Distributed by: